

Grilletes

SHACKLES / MANILLES




310




311



312



31..



32..



313



314



320



321

Grilletes standard

STANDARD SHACKLES / MANILLES STANDARD

6

Ref.	316	014	516	038	716	012	916	058	034	078	001	118	114	112	134	002	212
Ø	3/16	1/4	5/16	3/8	7/16	1/2	9/16	5/8	3/4	7/8	1	1 1/8	1 1/4	1 1/2	1 3/4	2	2 1/2
Ø mm	5	6	8	10	11	12	14	16	20	22	25	28	32	38	44	50	65
D	5	6	8	10	11	12	14	16	22	25	28	32	36	42	48	56	70
A	9	12	15	19	22	24	28	32	37	43	50	55	62	75	86	98	130
B	31..	19	24	31	40	44	48	54	64	75	80	100	104	116	148	171	200
	32..	20	24	32	43	44	50	62	67	86	90	102	116	124	155	175	198
C	15	19	22	28	35	35	39	45	60	63	72	82	100	110	120	137	190
Kgs.	31..	0,0145	0,029	0,063	0,100	0,152	0,205	0,303	0,471	1,074	1,436	2,075	3,06	4,20	7,25	12	16
	32..	0,0165	0,030	0,065	0,123	0,156	0,206	0,349	0,492	1,110	1,59	2,10	3,10	4,30	7,50	14	19
S.W.L. Kgs.	60	90	200	300	340	400	700	1.000	1.800	2.500	3.100	4.500	5.000	8.000	10.000	12.000	20.000
	50	25	20	10	10	10	5	5	2	1	1	-	-	-	-	-	-
	1.500	800	400	200	150	100	75	50	24	20	15	-	-	-	-	-	-




310A




31EA



311A



31..



32..



314A



320A



321A



324A

Grilletes de alta resistencia

U.S. Federal Specification

RR-CC-271

6

Ref.	A01	A15	A02	325	475	A65	A85	A95	A12	A17	A25	A35	A55	A80	A120
D	10	11	13	16	19	22	25	28	32	38	45	50	65	75	90
d	11	13	16	19	22	25	28	32	35	42	50	57	70	84	96
A	16	18	22	27	31	36	43	47	51	60	74	83	105	125	130
C 31...	31	37	43	51	59	73	85	90	94	127	149	171	203	-	-
C 32...	36	43	51	64	76	83	95	108	115	146	178	197	254	320	370
2R	26	29	32	43	51	58	68	75	83	99	126	146	185	220	229
Kgs.	31..	0,12	0,20	0,24	0,50	0,92	1,30	1,90	2,75	3,72	6,55	11	17,4	30	-
	32..	0,12	0,20	0,30	0,60	0,90	1,53	2	3	4	7,25	12,5	18,5	35	68
S.W.L. Tns.	1	1,5	2	3,25	4,75	6,5	8,5	9,5	12	17	25	35	55	85	120

S.W.L. Kgs. = Carga de trabajo / Safe working load / Charge de travail