

ESLINGAS DE POLIESTER

ESLINGAS TUBULARES DE POLIESTER SRS

- Programa SRS. En 1492-2
- Factor de Seguridad 7:1



PROTECCIONES



BEZLAR



PVC



BEZATEX

Código	Cód. color Norma CEN	Carga máx. de utiliz. kg	Ancho	Bezatex 2			
				a mm	i mm	h mm	w mm
3TSRS01	Violeta	1.000	45	80	70	17	5
3TSRS02	Verde	2.000	50	95	88	24	6
3TSRS03	Amarillo	3.000	63	110	100	17	5
3TSRS04	Gris	4.000	67	135	125	17	5
3TSRS05	Rojo	5.000	70	145	135	24	5
3TSRS06	Marrón	6.000	80	170	160	24	5
3TSRS08	Azul	8.000	100	200	190	24	5
3TSRS10	Naranja	10.000	100	230	220	38	5
3TSRS15	Naranja	15.000	105	290	280	30	8
3TSRS20	Naranja	20.000	128	330	320	45	8
3TSRS25	Naranja	25.000	141	330	320	50	8
3TSRS30	Naranja	30.000	160	330	320	50	8
3TSRS40	Naranja	40.000	173	330	320	50	8
3TSRS50	Naranja	50.000	230	370	350	50	8
3TSRS60	Naranja	60.000	245	370	350	50	8

CARGA MÁXIMA DE UTILIZACIÓN (Kg)

Código	Cod. color CEN	1 eslinga					2 eslingas		3 ó 4 eslingas	
		Tiro directo	Ahorcado	ángulos de inclinación b°			Ángulo de inclinación b°		Ángulo de inclinación b°	
				0°<b°<7°	7°<b°<45°	45°<b°<60°	0°<b°<45°	45°<b°<60°	0°<b°<45°	45°<b°<60°
		1	0,8	2	1,4	1	1,4	1	2,1	1,5

3TSRS01	Violeta	1.000	800	2.000	1.400	1.000	1.400	1.000	2.100	1.500
3TSRS02	Verde	2.000	1.600	4.000	2.800	2.000	2.800	2.000	4.200	3.000
3TSRS03	Amarillo	3.000	2.400	6.000	4.200	3.000	4.200	3.000	6.300	4.500
3TSRS04	Gris	4.000	3.200	8.000	5.600	4.000	5.600	4.000	8.400	6.000
3TSRS05	Rojo	5.000	4.000	10.000	7.000	5.000	7.000	5.000	10.500	7.500
3TSRS06	Marrón	6.000	4.800	12.000	8.400	6.000	8.400	6.000	12.600	9.000
3TSRS08	Azul	8.000	6.400	16.000	11.200	8.000	11.200	8.000	16.800	12.000
3TSRS10	Naranja	10.000	8.000	20.000	14.000	10.000	14.000	10.000	21.000	15.000
3TSRS15	Naranja	15.000	12.000	30.000	21.000	15.000	21.000	15.000	31.500	22.500
3TSRS20	Naranja	20.000	16.000	40.000	28.000	20.000	28.000	20.000	42.000	30.000
3TSRS25	Naranja	25.000	20.000	50.000	35.000	25.000	35.000	25.000	52.500	37.500
3TSRS30	Naranja	30.000	24.000	60.000	42.000	30.000	42.000	30.000	63.000	45.000
3TSRS40	Naranja	40.000	32.000	80.000	56.000	40.000	56.000	40.000	84.000	60.000
3TSRS50	Naranja	50.000	40.000	100.000	70.000	50.000	70.000	50.000	105.000	75.000
3TSRS60	Naranja	60.000	48.000	120.000	84.000	60.000	84.000	60.000	126.000	90.000

ESLINGAS DE POLIESTER

ESLINGAS TUBULARES DE POLIESTER SRG CON GAZAS

- Programa SRG. En 1492-2
- Factor de Seguridad 7:1



PROTECCIONES



BEZLAR



PVC



BEZATEX

Código	Cód. color Norma CEN	Carga máx. de utiliz. kg	a mm	Bezatex 2		
				i mm	h mm	w mm
3TSRG01	Violeta	1.000	80	70	17	5
3TSRG02	Verde	2.000	95	88	24	6
3TSRG03	Amarillo	3.000	110	100	17	5
3TSRG04	Gris	4.000	135	125	17	5
3TSRG05	Rojo	5.000	145	135	24	5
3TSRG06	Marrón	6.000	170	160	24	5
3TSRG08	Azul	8.000	200	190	24	5
3TSRG10	Naranja	10.000	230	220	38	5

CARGA MÁXIMA DE UTILIZACIÓN (Kg)

Código	Cod. color CEN	1 eslinga					2 eslingas		3 ó 4 eslingas	
		Tiro directo	Ahorcado	ángulos de inclinación b°			Ángulo de inclinación b°		Ángulo de inclinación b°	
				0<b°<7°	7°<b°<45°	45°<b°<60°	0°<b°<45°	45°<b°<60°	0°<b°<45°	45°<b°<60°
		1	0,8	2	1,4	1	1,4	1	2,1	1,5
3TSRRG01	Violeta	1.000	800	2.000	1.400	1.000	1.400	1.000	2.100	1.500
3TSRRG02	Verde	2.000	1.600	4.000	2.800	2.000	2.800	2.000	4.200	3.000
3TSRRG03	Amarillo	3.000	2.400	6.000	4.200	3.000	4.200	3.000	6.300	4.500
3TSRRG04	Gris	4.000	3.200	8.000	5.600	4.000	5.600	4.000	8.400	6.000
3TSRRG05	Rojo	5.000	4.000	10.000	7.000	5.000	7.000	5.000	10.500	7.500
3TSRRG06	Marrón	6.000	4.800	12.000	8.400	6.000	8.400	6.000	12.600	9.000
3TSRRG08	Azul	8.000	6.400	16.000	11.200	8.000	11.200	8.000	16.800	12.000
3TSRRG10	Naranja	10.000	8.000	20.000	14.000	10.000	14.000	10.000	21.000	15.000

ESLINGAS DE POLIESTER

DESPIECE DE SISTEMAS DE ELEVACIÓN

SRG-1/CLS



SRG-2/CLS



















SRG-4/CLS



SISTEMAS DE ELEVACIÓN SRG1. SRG2 Y SRG4. (Norma EN 1492 y DIN 61360)

CARGA MÁXIMA DE UTILIZACIÓN (Kg)

	1 ramal	2 ramales		4 ramales			
		Ángulos		Ángulos			
		-	0-45°	45-60°	-	0-45°	45-60°
							

Cod. color CEN	Mod. SRG1	Factor1	Mod. SRG2	Factor1,4	Factor1	Mod. SRG4	Factor2,1	Factor1,5
 Violeta	SRG1-1000	1000	SRG2-1000	1400	1000	SRG4-1000	2100	1500
 Verde	SRG1-2000	2000	SRG2-2000	2800	2000	SRG4-2000	4200	3000
 Amarillo	SRG1-3000	3000	SRG2-3000	4200	3000	SRG4-3000	6300	4500
 Gris	SRG1-4000	4000	SRG2-4000	5600	4000	SRG4-4000	8400	6000
 Rojo	SRG1-5000	5000	SRG2-5000	7000	5000	SRG4-5000	10500	7500
 Marrón	SRG1-6000	6000	SRG2-6000	8400	6000	SRG4-6000	12600	9000
 Azul	SRG1-8000	8000	SRG2-8000	11200	8000	SRG4-8000	16800	12000
 Naranja	SRG1-10000	10000	SRG2-10000	14000	10000	SRG4-10000	21000	15000
 Naranja	SRG1-15000	15000	SRG2-15000	21000	15000	SRG4-15000	31500	22500
 Naranja	SRG1-20000	20000	SRG2-20000	28000	20000	SRG4-20000	42000	30000
 Naranja	SRG1-25000	25000	SRG2-25000	35000	25000	SRG4-25000	52500	33500
 Naranja	SRG1-30000	30000	SRG2-30000	42000	30000	SRG4-30000	63000	45000
 Naranja	SRG1-40000	40000	SRG2-40000	56000	40000	SRG4-40000	84000	60000
 Naranja	SRG1-50000	50000	SRG2-50000	70000	50000	SRG4-50000	105000	75000