


Cáncamo zincado
EYE BOLTS. EYE NUTS
ANNEAUX DE LEVAGE



541 (DIN 580)



542 (DIN 582)

6	Ref. 541/542	006	008	010	012	016	020	022	024	030	036	042	048	056	064	072
	Ø	M-6	M-8	M-10	M-12	M-16	M-20	M-22	M-24	M-30	M-36	M-42	M-48	M-56	M-64	M-72
	B	13	13	17	20,5	27	30	33	36	45	54	63	68	78	90	100
	C	20	20	25	30	35	40	42	50	60	70	80	90	100	110	140
	⚖ Kgrs.	0,06	0,06	0,11	0,18	0,28	0,45	0,50	0,74	1,66	2,65	4,03	6,38	8,8	12,4	23,3
	S.W.L. Kgrs.	80	140	230	340	700	1.200	1.500	1.800	3.600	5.100	7.000	8.600	11.500	16.000	21.000
	S.W.L. Kgrs.	55	95	170	240	500	830	1.050	1.270	2.600	3.700	5.000	6.100	8.300	11.000	15.000

S.W.L. Kgrs. = Carga de trabajo / Safe working load / Charge de travail

[12]

Cáncamo macho - Inox
S.S. EYE BOLT
ANNEAU DE LEVAGE MÂLE - INOX
AISI 316



541I

6	Ref.	R	S.W.L.(Kgrs)
	541I06	M-6	80
	541I08	M-8	140
	541I10	M-10	230
	541I12	M-12	340
	541I16	M-16	700
	541I20	M-20	1.200
	541I24	M-24	1.800
	541I30	M-30	3.600
	541I36	M-36	5.100

Cáncamo hembra - Inox
S.S. EYE NUT
ANNEAU DE LEVAGE FEMELLE - INOX
AISI 316



542I

6	Ref.	R	S.W.L.(Kgrs)
	542I06	M-6	80
	542I08	M-8	140
	542I10	M-10	230
	542I12	M-12	340
	542I16	M-16	700
	542I20	M-20	1.200
	542I24	M-24	1.800
	542I30	M-30	3.600